

Конвейерные посудомоечные машины

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: sir@nt-rt.ru || сайт: <https://sammic.nt-rt.ru/>

RACK CONVEYOR DISHWASHER SRC-1800

67/100 baskets per hour (up to 1,800 plates/hour). Washing + rinsing.



SALES DESCRIPTION

Compact model for reduced space areas.
2 speeds.

- ✓ Fully stainless steel jacket.
- ✓ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

Economy

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- ✓ Programmed automatic stops if there is no loading.
- ✓ Stop and freezing of timer when the limit switch actuates.

Cleaning and maintenance

- ✓ Wide pivoting door allowing access for cleaning or inspection purpose.
- ✓ Detachable arms and dispersers for easier cleaning.
- ✓ Sloped removable stainless steel filters.
- ✓ Easy boiler emptying by loosening a hose.
- ✓ Failures are easily detected thanks to the warning lights.
- ✓ Easy to repair without moving the machine.

Washing

- ✓ Stainless steel wash arms and deep-drawn dispersers.
- ✓ Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dosifier intake in washing tank.

Rinsing

- ✓ Stainless steel rinse arms and powerful, stainless steel, deep-drawn dispersers.
- ✓ Automatic boiler filling with no failure risk for heating elements.
- ✓ Temperature control with high precision probes.

- ✓ Visualisation and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- ✓ Easy to install rinse aid dispenser intake in boiler.

INCLUDES

- ✓ 3 mixed baskets (plates).

OPTIONAL

- | | |
|--|--|
| ☐ Drying unit TS-600 / TS-90. | ☐ Inlet tables and compositions. |
| ☐ Extraction hood without motor CA. | ☐ Outlet tables and compositions. |
| ☐ Extraction hood with motor EV. | ☐ Option to ship the machine disassembled into two parts (see surcharge). |
| ☐ Extraction hood with steam condensation CV. | |

ACCESSORIES

- | | |
|---|---|
| ☐ Manual water softeners | ☐ Roller conveyor and corner roller conveyor (exit) |
| ☐ Automatic water softeners | ☐ Prewashing tables for pass-through and rack conveyor dishwashers |
| ☐ 500 x 500 mm baskets | ☐ CA Extraction hood for SRC-1800 (kit) |
| ☐ Loading table for corner situation for rack conveyor dishwashers | ☐ Logistical options and additional costs |
| ☐ Central sorting tables | |
| ☐ Single exit tables | |

SPECIFICATIONS

Basket dimensions: 500 x 500 mm
Useful height: 400 mm

Production

- ✓ Production baskets/hour: 100
- ✓ Production plates/hour: 1800

Wash

- ✓ Temperature: 55°C - 65°C
- ✓ Wash tank capacity: 80 l
- ✓ Pump: 2 Hp / 1500 W
- ✓ Wash heating element: 7500 W

Rinse

- ✓ Temperature: 80°C - 90°C
- ✓ Water consumption: 270 l/h
- ✓ Rinse heating element: 18000 W
- ✓ Boiler capacity: 20 l

Drag

- ✓ Drag motor power: 0.25 Hp / 180 W

Loading

- ✓ Central module total power: 27135 W

External dimensions (W x D x H)

- ✓ Width: 1180 mm
- ✓ Depth: 830 mm
- ✓ Height: 1430 mm

Net weight: 200 kg

Water Intake: 3/4”
Drain diameter: 1 1/2”
Noise level (1m.): 71 dB(A)

Optional accessories

- ✓ Lin. drying: TS-600
- ✓ Extraction: CA / EV / CV
- ✓ Tables

AVAILABLE MODELS

1302400	SRC-1800D 400/50/3N
1302401	SRC-1800D 220/60/3
1302450	Dishwasher SRC-1800D 380/60/3N
1302438	SRC-1800DCA 400/50/3N
1302413	SRC-1800DEV 400/50/3N
1302405	SRC-1800DCV 400/50/3N
1302406	SRC-1800DCV 220/60/3
1302403	SRC-1800DS6 400/50/3N
1302444	SRC-1800DS6 380/60/3N
1302404	SRC-1800DS6 220/60/3
1302440	SRC-1800DS6CA 400/50/3N
1302415	SRC-1800DS6EV 400/50/3N
1302407	SRC-1800DS6CV 400/50/3N
1302408	SRC-1800DS6CV 220/60/3
1302409	SRC-1800DS90 400/50/3N
1302442	SRC-1800DS90CA 400/50/3N
1302417	SRC-1800DS90EV 400/50/3N
1302411	SRC-1800DS90CV 400/50/3N
1302419	SRC-1800I 400/50/3N
1302420	SRC-1800I 220/60/3
1302445	SRC-1800ICA 400/50/3N
1302431	SRC-1800IEV 400/50/3N
1302423	SRC-1800ICV 400/50/3N
1302424	SRC-1800ICV 220/60/3
1302421	SRC-1800IS6 400/50/3N
1302422	SRC-1800IS6 220/60/3
1302447	SRC-1800IS6CA 400/50/3N
1302441	SRC-1800DS6CA 220/60/3
1302433	SRC-1800IS6EV 400/50/3N
1302425	SRC-1800IS6CV 400/50/3N
1302427	SRC-1800IS90 400/50/3N
1302449	SRC-1800IS90CA 400/50/3N
1302435	SRC-1800IS90EV 400/50/3N
1302429	SRC-1800IS90CV 400/50/3N
1302430	SRC-1800IS90CV 220/60/3

** Ask for special versions availability*

RACK CONVEYOR DISHWASHER SRC-2200

85/126 baskets per hour (up to 2,200 plates/hour). Washing + rinsing.



SALES DESCRIPTION

2 speeds.

- ✓ Fully stainless steel jacket.
- ✓ Inlet and outlet splash guards are standard.
- ✓ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

Economy

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- ✓ Programmed automatic stops if there is no loading.
- ✓ Stop and freezing of timer when the limit switch actuates.

Cleaning and maintenance

- ✓ Wide pivoting door allowing access for cleaning or inspection purpose.
- ✓ Detachable arms and dispersers for easier cleaning.
- ✓ Sloped removable stainless steel filters with independent removable basket.
- ✓ Easy boiler emptying by loosening a hose.
- ✓ Failures are easily detected thanks to the warning lights.
- ✓ Easy to repair without moving the machine.

Washing

- ✓ Stainless steel wash arms and deep-drawn dispersers.
- ✓ Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dispenser intake in washing tank.

Rinsing

- ✓ Stainless steel rinse arms and powerful, stainless steel, deep-drawn dispersers.
- ✓ Automatic boiler filling with no failure risk for heating elements.

- ✓ Temperature control with high precision probes.
- ✓ Visualisation and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- ✓ Easy to install rinse aid dispenser intake in boiler.

INCLUDES

- ✓ Inlet and outlet splash guards are standard.
- ✓ Extraction hood without motor
- CA.
- ✓ 3 mixed baskets (plates).

OPTIONAL

- ☐ Drying unit TS-600 / TS-90.
- ☐ Extraction hood with motor EV.
- ☐ Extraction hood with steam condensation CV.
- ☐ Inlet tables and compositions.
- ☐ Outlet tables and compositions.
- ☐ Option to ship the machine disassembled into two parts (see surcharge).

ACCESSORIES

- ☐ Manual water softeners
- ☐ Automatic water softeners
- ☐ 500 x 500 mm baskets
- ☐ Loading table for corner situation for rack conveyor dishwashers
- ☐ Central sorting tables
- ☐ Double connection central sorting table
- ☐ Single exit tables
- ☐ Roller conveyor and corner roller conveyor (exit)
- ☐ Machined curve (exit)
- ☐ Prewashing tables for pass-through and rack conveyor dishwashers
- ☐ Connecting tables for pass-through dishwashers and rack conveyors
- ☐ Logistical options and additional costs

SPECIFICATIONS

Basket dimensions: 500 x 500 mm
Useful height: 400 mm

Production

- ✓ Production baskets/hour: 85 / 126
- ✓ Production plates/hour: 1530 / 2200

Wash

- ✓ Temperature: 55°C - 65°C
- ✓ Wash tank capacity: 100 l
- ✓ Pump: 3 Hp / 2250 W
- ✓ Wash heating element: 9000 W

Rinse

- ✓ Temperature: 80°C - 90°C
- ✓ Water consumption: 300 l/h
- ✓ Rinse heating element: 18000 W
- ✓ Boiler capacity: 20 l

Drag

- ✓ Drag motor power: 0.25 Hp / 180 W

Loading

- ✓ Central module total power: 29580 W

External dimensions (W x D x H)

- ✓ Width: 1700 mm

- ✓ Depth: 829 mm
- ✓ Height: 1520 mm

Net weight: 250 kg

Water Intake: 3/4"

Drain diameter: 1 1/2"

Noise level (1m.): 71 dB(A)

Electrical supply:

Electrical connection: .

Please note: +3kW rinse heating element in models equipped with steam condenser.

AVAILABLE MODELS

1302507	SRC-2200DCA 400/50/3N
1302526	SRC-2200DCA 220/60/3
1302510	SRC-2200DEV 400/50/3N
1302503	SRC-2200DCV 400/50/3N
1302508	SRC-2200DS6CA 400/50/3N
1302529	SRC-2200DS6CA 400/50/3N
1302511	SRC-2200DS6EV 400/50/3N
1302504	SRC-2200DS6CV 400/50/3N
1302509	SRC-2200DS90CA 400/50/3N
1302512	SRC-2200DS90EV 400/50/3N
1302506	SRC-2200DS90CV 400/50/3N
1302519	SRC-2200ICA 400/50/3N
1302528	SRC-2200ICA 220/60/3
1302522	SRC-2200IEV 400/50/3N
1302516	SRC-2200ICV 400/50/3N
1302520	SRC-2200IS6CA 400/50/3N
1302525	SRC-2200IS6CA 220/60/3
1302527	SRC-2200IS6CA 220/50/3
1302523	SRC-2200IS6EV 400/50/3N
1302515	SRC-2200IS6CV 400/50/3N
1302521	SRC-2200IS90CA 400/50/3N
1302524	SRC-2200IS90EV 400/50/3N
1302518	SRC-2200IS90CV 400/50/3N

** Ask for special versions availability*

RACK CONVEYOR DISHWASHER SRC-2700

100/150 baskets per hour (up to 2,700 plates/hour). Washing + rinsing.



SALES DESCRIPTION

2 speeds.

- ✓ Fully stainless steel jacket.
- ✓ Inlet and outlet splash guards are standard.
- ✓ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

Economy

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- ✓ Programmed automatic stops if there is no loading.
- ✓ Stop and freezing of timer when the limit switch actuates.

Cleaning and maintenance

- ✓ Wide pivoting door allowing access for cleaning or inspection purpose.
- ✓ Detachable arms and dispersers for easier cleaning.
- ✓ Sloped removable stainless steel filters with independent removable basket.
- ✓ Easy boiler emptying by loosening a hose.
- ✓ Failures are easily detected thanks to the warning lights.
- ✓ Easy to repair without moving the machine.

Washing

- ✓ Stainless steel wash arms and deep-drawn dispersers.
- ✓ Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dispenser intake in washing tank.

Rinsing

- ✓ Stainless steel rinse arms and powerful, stainless steel, deep-drawn dispersers.
- ✓ Automatic boiler filling with no failure risk for heating elements.

- ✓ Temperature control with high precision probes.
- ✓ Visualisation and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- ✓ Easy to install rinse aid dispenser intake in boiler.

INCLUDES

- ✓ Inlet and outlet splash guards are standard.
- ✓ Extraction hood without motor
- CA.
- ✓ 3 mixed baskets (plates).

OPTIONAL

- ☐ Drying unit TS-600 / TS-90.
- ☐ Extraction hood with motor EV.
- ☐ Extraction hood with steam condensation CV.
- ☐ Inlet tables and compositions.
- ☐ Outlet tables and compositions.
- ☐ Option to ship the machine disassembled into two parts (see surcharge).

ACCESSORIES

- ☐ Manual water softeners
- ☐ Automatic water softeners
- ☐ 500 x 500 mm baskets
- ☐ Loading table for corner situation for rack conveyor dishwashers
- ☐ Central sorting tables
- ☐ Double connection central sorting table
- ☐ Single exit tables
- ☐ Roller conveyor and corner roller conveyor (exit)
- ☐ Machined curve (exit)
- ☐ Prewashing tables for pass-through and rack conveyor dishwashers
- ☐ Connecting tables for pass-through dishwashers and rack conveyors
- ☐ Logistical options and additional costs

SPECIFICATIONS

Basket dimensions: 500 x 500 mm
Useful height: 400 mm

Production

- ✓ Production baskets/hour: 100 / 150
- ✓ Production plates/hour: 1800 / 2700

Wash

- ✓ Temperature: 55°C - 65°C
- ✓ Wash tank capacity: 100 l
- ✓ Pump: 3.2 Hp / 2400 W

Rinse

- ✓ Temperature: 80°C - 90°C
- ✓ Water consumption: 330 l/h
- ✓ Rinse heating element: 18000 W
- ✓ Boiler capacity: 20 l

Drag

- ✓ Drag motor power: 0.25 Hp / 180 W

Loading

- ✓ Central module total power: 29780 W

External dimensions (W x D x H)

- ✓ Width: 1700 mm
- ✓ Depth: 829 mm

✓ Height: 1520 mm

Net weight: 250 kg

Water Intake: 3/4"

Drain diameter: 1 1/2"

Noise level (1m.): 71 dB(A)

Optional accessories

✓ Lin. drying: TS-600

✓ Extraction: CA / EV / CV

✓ Tables

Please note: +3kW rinse heating element in models equipped with steam condenser.

AVAILABLE MODELS

1302557	SRC-2700DCA 400/50/3N
1302578	Dishwasher SRC-2700DCA 220/60/3
1302560	SRC-2700DEV 400/50/3N
1302553	SRC-2700DCV 400/50/3N
1302558	SRC-2700DS6CA 400/50/3N
1302580	SRC-2700DS6CA 220/60/3
1302561	SRC-2700DS6EV 400/50/3N
1302554	SRC-2700DS6CV 400/50/3N
1302555	SRC-2700DS8CA 400/50/3N
1302559	SRC-2700DS90CA 400/50/3N
1302562	SRC-2700DS90EV 400/50/3N
1302556	SRC-2700DS90CV 400/50/3N
1302569	SRC-2700ICA 400/50/3N
1302576	SRC-2700ICA 220/60/3
1302572	SRC-2700IEV 400/50/3N
1302565	SRC-2700ICV 400/50/3N
1302570	SRC-2700IS6CA 400/50/3N
1302575	SRC-2700IS6CA 220/60/3
1302577	SRC-2700IS6CA 380/60/3N
1302573	SRC-2700IS6EV 400/50/3N
1302566	SRC-2700IS6CV 400/50/3N
1302579	Dishwasher SRC-2700IS8CA 400/50/3N
1302571	SRC-2700IS90CA 400/50/3N
1302574	SRC-2700IS90EV 400/50/3N
1302568	SRC-2700IS90CV 400/50/3N

** Ask for special versions availability*

RACK CONVEYOR DISHWASHER SRC-3300

122/183 baskets per hour (up to 3,300 plates/hour). Enhanced washing + double rinsing.



SALES DESCRIPTION

2 speeds.

- ✓ Fully stainless steel jacket.
- ✓ Inlet and outlet splash guards are standard.
- ✓ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

Economy

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- ✓ Programmed automatic stops if there is no loading.
- ✓ Stop and freezing of timer when the limit switch actuates.

Cleaning and maintenance

- ✓ Wide pivoting door allowing access for cleaning or inspection purpose.
- ✓ Detachable arms and dispersers for easier cleaning.
- ✓ Sloped removable stainless steel filters with independent removable basket.
- ✓ Easy boiler emptying by loosening a hose.
- ✓ Failures are easily detected thanks to the warning lights.
- ✓ Easy to repair without moving the machine.

Washing

- ✓ Stainless steel wash arms and deep-drawn dispersers.
- ✓ Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dispenser intake in washing tank.

Rinsing

- ✓ Stainless steel rinse arms and powerful, stainless steel, deep-drawn dispersers.
- ✓ Automatic boiler filling with no failure risk for heating elements.

- ✓ Temperature control with high precision probes.
- ✓ Visualization and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- ✓ Easy to install rinse aid dispenser intake in boiler.

INCLUDES

- ✓ Inlet and outlet splash guards are standard.
- ✓ Extraction hood without motor
- CA.
- ✓ 3 mixed baskets (plates).

OPTIONAL

- ☐ Drying unit TS-600 / TS-90.
- ☐ Extraction hood with motor EV.
- ☐ Extraction hood with steam condensation CV.
- ☐ Inlet tables and compositions.
- ☐ Outlet tables and compositions.
- ☐ Option to ship the machine disassembled into two or three parts (see surcharges).

ACCESSORIES

- ☐ Manual water softeners
- ☐ Automatic water softeners
- ☐ 500 x 500 mm baskets
- ☐ Loading table for corner situation for rack conveyor dishwashers
- ☐ Central sorting tables
- ☐ Double connection central sorting table
- ☐ Single exit tables
- ☐ Roller conveyor and corner roller conveyor (exit)
- ☐ Machined curve (exit)
- ☐ Prewashing tables for pass-through and rack conveyor dishwashers
- ☐ Connecting tables for pass-through dishwashers and rack conveyors
- ☐ Logistical options and additional costs

SPECIFICATIONS

Basket dimensions: 500 x 500 mm

Useful height: 400 mm

Production

- ✓ Production baskets/hour: 122 / 183
- ✓ Production plates/hour: 2196 / 3294

Wash

- ✓ Temperature: 55°C - 65°C
- ✓ Wash tank capacity: 100 l
- ✓ Pump: 3.5 Hp / 2600 W
- ✓ Wash heating element: 9000 W

Pre-rinse

- ✓ Temperature: 65°C - 75°C
- ✓ Pre-rinse basin capacity: 15 l
- ✓ Pump: 0.2 Hp / 150 W
- ✓ Pre-rinse heating element: 6000 W

Rinse

- ✓ Temperature: 80°C - 90°C
- ✓ Water consumption: 330 l/h
- ✓ Rinse heating element: 18000 W
- ✓ Boiler capacity: 20 l

Drag

✓ Drag motor power: 0.25 Hp / 180 W

Loading

✓ Central module total power: 30270 W

External dimensions (W x D x H)

✓ Width: 2300 mm

✓ Depth: 829 mm

✓ Height: 1520 mm

Net weight: 410 kg

Water Intake: 3/4”

Drain diameter: 1 1/2”

Noise level (1m.): 71 dB(A)

Please note: +3kW rinse heating element in models equipped with steam condenser.

AVAILABLE MODELS

1302610	SRC-3300DCA 400/50/3N
1302607	SRC-3300DEV 400/50/3N
1302603	SRC-3300DCV 400/50/3N
1302611	SRC-3300DS6CA 400/50/3N
1302608	SRC-3300DS6EV 400/50/3N
1302604	SRC-3300DS6CV 400/50/3N
1302612	SRC-3300DS90CA 400/50/3N
1302609	SRC-3300DS90EV 400/50/3N
1302606	SRC-3300DS90CV 400/50/3N
1302630	SRC-3300DS8CA 400/50/3N
1302622	SRC-3300ICA 400/50/3N
1302628	SRC-3300ICA 220/60/3
1302619	SRC-3300IEV 400/50/3N
1302615	SRC-3300ICV 400/50/3N
1302623	SRC-3300IS6CA 400/50/3N
1302626	SRC-3300IS6CA 220/60/3
1302620	SRC-3300IS6EV 400/50/3N
1302616	SRC-3300IS6CV 400/50/3N
1302625	SRC-3300IS8CA 400/50/3N
1302632	SRC-3300IS8EV 400/50/3N
1302624	SRC-3300IS90CA 400/50/3N
1302621	SRC-3300IS90EV 400/50/3N
1302618	SRC-3300IS90CV 400/50/3N

** Ask for special versions availability*

RACK CONVEYOR DISHWASHER SRC-3600

130/200 baskets per hour (up to 3,600 plates/hour). Pre-washing + washing + rinsing.



SALES DESCRIPTION

2 speeds.

- ✓ Fully stainless steel jacket.
- ✓ Inlet and outlet splash guards are standard.
- ✓ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

Economy

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- ✓ Programmed automatic stops if there is no loading.
- ✓ Stop and freezing of timer when the limit switch actuates.

Cleaning and maintenance

- ✓ Wide pivoting door allowing access for cleaning or inspection purpose.
- ✓ Detachable arms and dispersers for easier cleaning.
- ✓ Sloped removable stainless steel filters with independent removable basket.
- ✓ Easy boiler emptying by loosening a hose.
- ✓ Failures are easily detected thanks to the warning lights.
- ✓ Easy to repair without moving the machine.

Washing

- ✓ Stainless steel wash arms and deep-drawn dispersers.
- ✓ Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dispenser intake in washing tank.

Rinsing

- ✓ Stainless steel rinse arms and powerful, stainless steel, deep-drawn dispersers.
- ✓ Automatic boiler filling with no failure risk for heating elements.

- ✓ Temperature control with high precision probes.
- ✓ Visualisation and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- ✓ Easy to install rinse aid dispenser intake in boiler.

INCLUDES

- ✓ Inlet and outlet splash guards are standard.
- ✓ Extraction hood without motor
- CA.
- ✓ 3 mixed baskets (plates).

OPTIONAL

- ☐ Drying unit TS-600 / TS-800 / TS-90.
- ☐ Extraction hood with motor EV.
- ☐ Extraction hood with steam condensation CV.
- ☐ Inlet tables and compositions.
- ☐ Outlet tables and compositions.
- ☐ Option to ship the machine disassembled into two or three parts (see surcharges).

ACCESSORIES

- ☐ Manual water softeners
- ☐ Automatic water softeners
- ☐ 500 x 500 mm baskets
- ☐ Loading table for corner situation for rack conveyor dishwashers
- ☐ Central sorting tables
- ☐ Double connection central sorting table
- ☐ Single exit tables
- ☐ Roller conveyor and corner roller conveyor (exit)
- ☐ Machined curve (exit)
- ☐ Prewashing tables for pass-through and rack conveyor dishwashers
- ☐ Connecting tables for pass-through dishwashers and rack conveyors
- ☐ Logistical options and additional costs

SPECIFICATIONS

Basket dimensions: 500 x 500 mm

Useful height: 400 mm

Production

- ✓ Production baskets/hour: 130-200
- ✓ Production plates/hour: 2340-3600

Pre-wash

- ✓ Temperature: 35°C - 45°C
- ✓ Pre-wash basin capacity: 60 l
- ✓ Pump: 1.2 Hp / 880 W

Wash

- ✓ Temperature: 55°C - 65°C
- ✓ Wash tank capacity: 100 l
- ✓ Pump: 3.2 Hp / 2400 W
- ✓ Wash heating element: 9000 W

Rinse

- ✓ Temperature: 80°C - 90°C
- ✓ Water consumption: 390 l/h
- ✓ Rinse heating element: 21000 W
- ✓ Boiler capacity: 20 l

Drag

✓ Drag motor power: 0.25 Hp / 180 W

Loading

✓ Total installed power: 33460 W

External dimensions (W x D x H)

✓ Width: 2300 mm

✓ Depth: 829 mm

✓ Height: 1520 mm

Net weight: 400 kg

Water Intake: 3/4"

Drain diameter: 1 1/2"

Noise level (1m.): 71 dB(A)

Please note: +3kW rinse heating element in models equipped with steam condenser.

AVAILABLE MODELS

1302660	SRC-3600DCA 400/50/3N
1302690	SRC-3600DCA 380/60/3
1302657	SRC-3600DEV 400/50/3N
1302653	SRC-3600DCV 400/50/3N
1302661	SRC-3600DS6CA 400/50/3N
1302658	SRC-3600DS6EV 400/50/3N
1302654	SRC-3600DS6CV 400/50/3N
1302686	SRC-3600DS6CV 220/60/3
1302688	SRC-3600DS6CV 380/60/3
1302663	SRC-3600DS8CA 400/50/3N
1302666	SRC-3600DS8CA 220/60/3
1302665	SRC-3600DS8EV 400/50/3N
1302664	SRC-3600DS8CV 400/50/3
1302662	SRC-3600DS90CA 400/50/3N
1302659	SRC-3600DS90EV 400/50/3N
1302656	SRC-3600DS90CV 400/50/3N
1302676	SRC-3600ICA 400/50/3N
1302685	SRC-3600ICA 220/60/3
1302673	SRC-3600IEV 400/50/3N
1302669	SRC-3600ICV 400/50/3N
1302677	SRC-3600IS6CA 400/50/3N
1302683	SRC-3600IS6CA 220/60/3
1302674	SRC-3600IS6EV 400/50/3N
1302672	SRC-3600IS6CV 400/50/3N
1302687	SRC-3600IS6CV 220/60/3
1302689	SRC-3600IS6CV 380/60/3
1302679	SRC-3600IS8CA 400/50/3N
1302682	SRC-3600IS8CA 220/60/3
1302681	SRC-3600IS8EV 400/50/3N
1302680	SRC-3600IS8CV 400/50/3N
1302678	SRC-3600IS90CA 400/50/3N
1302675	SRC-3600IS90EV 400/50/3N
1302670	SRC-3600IS90CV 400/50/3N

** Ask for special versions availability*

RACK CONVEYOR DISHWASHER SRC-4000

150/225 baskets per hour (up to 4,050 plates/hour). Pre-washing + enhanced washing + double rinsing.



SALES DESCRIPTION

2 speeds.

- ✓ Fully stainless steel jacket.
- ✓ Inlet and outlet splash guards are standard.
- ✓ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

Economy

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- ✓ Programmed automatic stops if there is no loading.
- ✓ Stop and freezing of timer when the limit switch actuates.

Cleaning and maintenance

- ✓ Wide pivoting door allowing access for cleaning or inspection purpose.
- ✓ Detachable arms and dispersers for easier cleaning.
- ✓ Sloped removable stainless steel filters with independent removable basket.
- ✓ Easy boiler emptying by loosening a hose.
- ✓ Failures are easily detected thanks to the warning lights.
- ✓ Easy to repair without moving the machine.

Washing

- ✓ Stainless steel wash arms and deep-drawn dispersers.
- ✓ Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dispenser intake in washing tank.

Rinsing

- ✓ Stainless steel rinse arms and powerful, stainless steel, deep-drawn dispersers.
- ✓ Automatic boiler filling with no failure risk for heating elements.

- ✓ Temperature control with high precision probes.
- ✓ Visualisation and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- ✓ Easy to install rinse aid dispenser intake in boiler.

INCLUDES

- ✓ Inlet and outlet splash guards are standard.
- ✓ Extraction hood without motor CA.
- ✓ 3 mixed baskets (plates).

OPTIONAL

- ☐ Drying unit TS-800.
- ☐ Drying unit TS-90.
- ☐ Extraction hood with motor EV.
- ☐ Extraction hood with steam condensation CV.
- ☐ Inlet tables and compositions.
- ☐ Outlet tables and compositions.
- ☐ Option to ship the machine disassembled into two or three parts (see surcharges).

ACCESSORIES

- ☐ Manual water softeners
- ☐ Automatic water softeners
- ☐ 500 x 500 mm baskets
- ☐ Loading table for corner situation for rack conveyor dishwashers
- ☐ Central sorting tables
- ☐ Double connection central sorting table
- ☐ Single exit tables
- ☐ Roller conveyor and corner roller conveyor (exit)
- ☐ Machined curve (exit)
- ☐ Prewashing tables for pass-through and rack conveyor dishwashers
- ☐ Connecting tables for pass-through dishwashers and rack conveyors
- ☐ Logistical options and additional costs

SPECIFICATIONS

Basket dimensions: 500 x 500 mm
Useful height: 400 mm

Production

- ✓ Production baskets/hour: 150 / 225
- ✓ Production plates/hour: 2700 / 4050

Pre-wash

- ✓ Temperature: 35°C - 45°C
- ✓ Pre-wash basin capacity: 60 l
- ✓ Pump: 1.2 Hp / 880 W

Boosted wash

- ✓ Temperature: 55°C - 65°C
- ✓ Wash tank capacity: 100 l
- ✓ Pump: 3.5 Hp / 2600 W
- ✓ Wash heating element: 9000 W

Pre-rinse

- ✓ Temperature: 65°C - 75°C
- ✓ Pre-rinse basin capacity: 15 l
- ✓ Pump: 0.2 Hp / 0.15 W
- ✓ Pre-rinse heating element: 6000 W

Rinse

- ✓ Temperature: 80°C - 90°C
- ✓ Water consumption: 390 l/h
- ✓ Rinse heating element: 21000 W
- ✓ Boiler capacity: 20 l

Drag

- ✓ Drag motor power: 0.25 Hp / 180 W

Loading

- ✓ Total installed power: 39810 W

External dimensions (W x D x H)

- ✓ Width: 2900 mm
- ✓ Depth: 829 mm
- ✓ Height: 1520 mm

Net weight: 450 kg

Water Intake: 3/4"

Drain diameter: 1 1/2"

Noise level (1m.): 71 dB(A)

Please note: +3kW rinse heating element in models equipped with steam condenser.

AVAILABLE MODELS

1302740	SRC-4000DCA 400/50/3N
1302767	SRC-4000DCA 220/60/3
1302737	SRC-4000DEV 400/50/3N
1302733	SRC-4000DCV 400/50/3N
1302746	SRC-4000DS8CA 400/50/3N
1302764	SRC-4000DS8CA 220/60/3
1302766	SRC-4000DS8CA 380/60/3N
1302745	SRC-4000DS8EV 400/50/3N
1302744	SRC-4000DS8CV 400/50/3N
1302765	SRC-4000DS8CV 380/60/3N
1302742	SRC-4000DS90CA 400/50/3N
1302736	SRC-4000DS90CV 400/50/3N
1302756	SRC-4000ICA 400/50/3N
1302753	SRC-4000IEV 400/50/3N
1302749	SRC-4000ICV 400/50/3N
1302763	SRC-4000IS8CA 400/50/3N
1302762	SRC-4000IS8CA 220/60/3
1302761	SRC-4000IS8EV 400/50/3N
1302760	SRC-4000IS8CV 400/50/3N
1302758	SRC-4000IS90CA 400/50/3N
1302752	SRC-4000IS90CV 400/50/3N

** Ask for special versions availability*

RACK CONVEYOR DISHWASHER SRC-5000

183/275 baskets per hour (up to 4,950 plates/hour). Pre-washing + first washing + enhanced washing + double rinsing.



SALES DESCRIPTION

2 speeds.

- ✓ Fully stainless steel jacket.
- ✓ Inlet and outlet splash guards are standard.
- ✓ Stainless steel central rack feed system.
- ✓ Process cycles are divided by rubber curtains.
- ✓ Automatic cycle start.

Economy

- ✓ Energy saving rinse supply switch.
- ✓ Pressure controller in the rinse section to limit consumption.
- ✓ Programmed automatic stops if there is no loading.
- ✓ Stop and freezing of timer when the limit switch actuates.

Cleaning and maintenance

- ✓ Wide pivoting door allowing access for cleaning or inspection purpose.
- ✓ Detachable arms and dispersers for easier cleaning.
- ✓ Sloped removable stainless steel filters with independent removable basket.
- ✓ Easy boiler emptying by loosening a hose.
- ✓ Failures are easily detected thanks to the warning lights.
- ✓ Easy to repair without moving the machine.

Washing

- ✓ Stainless steel wash arms and deep-drawn dispersers.
- ✓ Efficient and durable wash arm dispersers.
- ✓ Powerful, self-draining vertical wash pump.
- ✓ Easy to install detergent dispenser intake in washing tank.

Rinsing

- ✓ Stainless steel rinse arms and powerful, stainless steel, deep-drawn dispersers.
- ✓ Automatic boiler filling with no failure risk for heating elements.

- ✓ Temperature control with high precision probes.
- ✓ Visualisation and adjustment of washing and rinsing temperatures in the digital display by pressing a button.
- ✓ Easy to install rinse aid dispenser intake in boiler.

INCLUDES

- ✓ Inlet and outlet splash guards are standard.
- ✓ Extraction hood without motor
- CA.
- ✓ 3 mixed baskets (plates).

OPTIONAL

- ☐ Drying unit TS-800 / TS-90.
- ☐ Extraction hood with motor EV.
- ☐ Extraction hood with steam condensation CV.
- ☐ Inlet tables and compositions.
- ☐ Outlet tables and compositions.
- ☐ Option to ship the machine disassembled into two or three parts (see surcharges).

ACCESSORIES

- ☐ Manual water softeners
- ☐ Automatic water softeners
- ☐ 500 x 500 mm baskets
- ☐ Loading table for corner situation for rack conveyor dishwashers
- ☐ Central sorting tables
- ☐ Double connection central sorting table
- ☐ Single exit tables
- ☐ Roller conveyor and corner roller conveyor (exit)
- ☐ Machined curve (exit)
- ☐ Prewashing tables for pass-through and rack conveyor dishwashers
- ☐ Connecting tables for pass-through dishwashers and rack conveyors
- ☐ Logistical options and additional costs

SPECIFICATIONS

Basket dimensions: 500 x 500 mm

Useful height: 400 mm

Production

- ✓ Production baskets/hour: 183 / 275
- ✓ Production plates/hour: 3294 / 4950

Pre-wash

- ✓ Temperature: 35°C - 45°C
- ✓ Pre-wash basin capacity: 60 l
- ✓ Pump: 1.2 Hp / 880 W

First wash

- ✓ Temperature: 55°C - 65°C
- ✓ 1st wash tank capacity: 60 l
- ✓ Pump: 1.2 Hp / 880 W
- ✓ 1st wash heating element: 6000 W

Boosted wash

- ✓ Temperature: 55°C - 65°C
- ✓ Wash tank capacity: 100 l
- ✓ Pump: 3.5 Hp / 2600 W
- ✓ Wash heating element: 9000 W

Pre-rinse

- ✓ Temperature: 65°C - 75°C



- ✓ Pre-rinse basin capacity: 15 l
- ✓ Pump: 0.2 Hp / 0.15 W
- ✓ Pre-rinse heating element: 6000 W

Rinse

- ✓ Temperature: 80°C - 90°C
- ✓ Water consumption: 480 l/h
- ✓ Rinse heating element: 27000 W
- ✓ Boiler capacity: 20 l

Drag

- ✓ Drag motor power: 0.25 Hp / 180 W

Loading

- ✓ Central module total power: 52790 W

External dimensions (W x D x H)

- ✓ Width: 3500 mm
- ✓ Depth: 829 mm
- ✓ Height: 1520 mm

Net weight: 540 kg

Water Intake: 3/4"

Drain diameter: 1 1/2"

Noise level (1m.): 71 dB(A)

Please note: +3kW rinse heating element in models equipped with steam condenser.

Crated dimensions
4370 x 980 x 2000 mm

AVAILABLE MODELS

1302807	SRC-5000DCA 400/50/3N
1302805	SRC-5000DEV 400/50/3N
1302802	SRC-5000DCV 400/50/3N
1302812	SRC-5000DS8CA 400/50/3N
1302827	SRC-5000DS8CA 220/60/3
1302811	SRC-5000DS8EV 400/50/3N
1302810	SRC-5000DS8CV 400/50/3N
1302806	SRC-5000DS90EV 400/50/3N
1302819	SRC-5000ICA 400/50/3N
1302817	SRC-5000IEV 400/50/3N
1302814	SRC-5000ICV 400/50/3N
1302825	SRC-5000IS8CA 400/50/3N
1302826	SRC-5000IS8CA 220/60/3
1302824	SRC-5000IS8EV 400/50/3N
1302822	SRC-5000IS8CV 400/50/3N
1302823	SRC-5000IS8CV 380/60/3
1302818	SRC-5000IS90EV 400/50/3N

** Ask for special versions availability*



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04	Иваново (4932)77-34-06	Магнитогорск (3519)55-03-13	Ростов-на-Дону (863)308-18-15	Тольятти (8482)63-91-07
Ангарск (3955)60-70-56	Ижевск (3412)26-03-58	Москва (495)268-04-70	Рязань (4912)46-61-64	Томск (3822)98-41-53
Архангельск (8182)63-90-72	Иркутск (395)279-98-46	Мурманск (8152)59-64-93	Самара (846)206-03-16	Тула (4872)33-79-87
Астрахань (8512)99-46-04	Казань (843)206-01-48	Набережные Челны (8552)20-53-41	Санкт-Петербург (812)309-46-40	Тюмень (3452)66-21-18
Барнаул (3852)73-04-60	Калининград (4012)72-03-81	Нижний Новгород (831)429-08-12	Саратов (845)249-38-78	Ульяновск (8422)24-23-59
Белгород (4722)40-23-64	Калуга (4842)92-23-67	Новокузнецк (3843)20-46-81	Севастополь (8692)22-31-93	Улан-Удэ (3012)59-97-51
Благовещенск (4162)22-76-07	Кемерово (3842)65-04-62	Ноябрьск (3496)41-32-12	Саранск (8342)22-96-24	Уфа (347)229-48-12
Брянск (4832)59-03-52	Киров (8332)68-02-04	Новосибирск (383)227-86-73	Симферополь (3652)67-13-56	Хабаровск (4212)92-98-04
Владивосток (423)249-28-31	Коломна (4966)23-41-49	Омск (3812)21-46-40	Смоленск (4812)29-41-54	Чебоксары (8352)28-53-07
Владикавказ (8672)28-90-48	Кострома (4942)77-07-48	Орел (4862)44-53-42	Сочи (862)225-72-31	Челябинск (351)202-03-61
Владимир (4922)49-43-18	Краснодар (861)203-40-90	Оренбург (3532)37-68-04	Ставрополь (8652)20-65-13	Череповец (8202)49-02-64
Волгоград (844)278-03-48	Красноярск (391)204-63-61	Пенза (8412)22-31-16	Сургут (3462)77-98-35	Чита (3022)38-34-83
Вологда (8172)26-41-59	Курск (4712)77-13-04	Петрозаводск (8142)55-98-37	Сыктывкар (8212)25-95-17	Якутск (4112)23-90-97
Воронеж (473)204-51-73	Курган (3522)50-90-47	Псков (8112)59-10-37	Тамбов (4752)50-40-97	Ярославль (4852)69-52-93
Екатеринбург (343)384-55-89	Липецк (4742)52-20-81	Пермь (342)205-81-47	Тверь (4822)63-31-35	

Россия +7(495)268-04-70	Казахстан +(727)345-47-04	Беларусь +(375)257-127-884	Узбекистан +998(71)205-18-59	Киргизия +996(312)96-26-47
-------------------------	---------------------------	----------------------------	------------------------------	----------------------------